

Interactive Flat Panel IFM55TH652/4

VESTEL



Key Features



Crestron Connected certification complements VESTEL's presence with inside the corporate, retail, government, better training and hospitality markets, all of which use expert AV controls. As those sectors hold to evolve with growing necessities for simple-to-use merchandise, seamless integration, dependable answers and community connectivity.

16h



400



Display

Screen Size	55"
Panel Technology	IPS
Backlight Type	Direct-Type LED
Brightness (typical)	400 cd/m ²
Native Resolution	UHD: 3840 x 2160 - HDR10
Contrast Ratio (typical)	1300:1
Dynamic Contrast Ratio	40000:1
Panel Life Time (Min.)	30000 Hr
Response Time (typical)	6 ms
Active Area (H x V)	1210 x 681 mm
Viewing Angle	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10
Color Value	16.7 M (8-bit)
Screen Treatment	2H
Haze Level	8%
Refresh Rate	60 Hz
Front Type	Black Super Narrow Bezel
Orientation	Horizontal
Operation Hours	16/7
Area of Usage	Indoor

Built-in System

Mainboard Model	17MB135VS
-----------------	-----------

Rear I/Os

RGB Input	VGA(DE-15F)
RGB Output	N/A
Video Input	4xHDMI2.0, 2xUSB2.0, USB2.0(Internal)
Video Output	HDMI2.0
Audio Input	Line In L/R
Audio Output	Headphone, Optic SPDIF
External Control	RS232(DE-9F), Ethernet(RJ45), Service(RJ12)
External Sensor	RJ12

Touch Interactivity

Type of Touch Technology	Infrared (IR) Technology
Continuous Touch Points	10 Points
Sensitivity	Any touch with finger, gloved hand or pointer
Connectivity	HID, TUIO, Flash
Compatibility	Windows®7, Windows®8, Windows®10, Vista, XP, Mac® OS, Linux, Android
Orientation	Landscape support

Calibration	No need
Accuracy	%90 <
Reporting Rate	Up to 450 fps
Glass Type	Anti Glared (AG), 4mm Tempered
Frame Rate	up to 450 fps
Communication	USB 2.0
Power Supply Mode	USB
Supply Voltage	DC 5V +/- 5%
Average Current	<400mA
Response Time	<10ms
Touch Accuracy	+/-2mm (over 90% area)
Touch Durability	Unlimited
HID Compatibility	Yes USB
Object Sizes for Touch	5mm

Mechanical

Product Dimensions (WxDxH)	1280 x 123 x 751 mm
Package Dimensions (WxDxH)	1480 x 265 x 930 mm
Product Weight	29.45 kg
Package Weight	38.15 kg
Vesa Mounting	400 x 200 mm
Bezel Width	B:34 T:34 L/R:34 mm

Environmental Conditions

Operating Temperature	+40°C / 0°C
Operating Humidity	90%

Power

Power Supply	110 VAC - 240 VAC
--------------	-------------------

Power Consumption

Typical	138 W
Maximum	180 W
Deep Standby	≤0.5W

Features

Main Features	USB-Autoplay, Auto-switch on Failover, Control Button Lock, HDMI Wake-Up
Mechanical Features	IR Touch, Joystick, IR Extender Support, Rocker Switch, Detachable power cable, Carrying handles, Detachable logo positioning, Cable Holders
Optional Features	OPS Compliance
Speaker	2 x 8 W

Accessory

Standard	QSG, IB, Power Cord, Remote Control, RC Battery, Mounting Kit, Extension Brackets, IR Extender Cable
----------	---

Certification

Safety	YES
EMC	YES
CE	YES
Reability Approval	YES