



## Key Features



This series features wired and wireless connectivity such as embedded WiFi and Bluetooth. Due to the wireless capabilities, the displays can easily gather their content without any external device. Moreover, WiFi allows screen sharing to be enjoyed with Miracast.




This series lets your USB and your content to be secured within the back cover of the display. The cover is protected with a screw not allowing any outside intervention.



You will be able to show photo and video content automatically with USB Auto-play feature. SoC software gives you a choice to turn on USB auto-play function making it easy for end-users to show any media on the screen and not worry about anything else.



This series' displays exhibit ultra narrow bezel design eliminating the visual superfluties, directing audience focus on your advertised content. This series is found to be desirable for digital signage specific design: internal usb cover, OPS-slot, detachable power plug, carrying handles and IR extender.



With quad core SoC (System on Chip), this Series displays are the digital signage monitors for both offline designed content and cloud-based managed content. This helps your digital content to be displayed in the displays by content management systems.



Our displays have a protection for "No Signal". If the source is disconnected, the display will either show your customized banner or search for any other signal from video sources. Since blank screen is the worst case scenario for advertisement, failover is one of the critical feature in our signage displays.

## Display

Screen Size	43"
Panel Technology	IPS
Backlight Type	Slim DLED
Brightness (typical)	500 cd/m <sup>2</sup>
Native Resolution	3840 x 2160 (16:9) - UHD
Contrast Ratio (typical)	1200:1 (typ.)
Dynamic Contrast Ratio	50000:1
Panel Life Time ( Min. )	30000 Hrs
Response Time (typical)	8 ms
Active Area (H x V)	941.1 (H) x 529.4 (V) mm
Viewing Angle	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10
Color Value	1.07G (8bits + FRC)
Color Gamut	72% NTSC
Haze Level	1%
Refresh Rate	60 Hz
Orientation	Landscape / Portrait
Operation Hours	24/7
Area of Usage	Indoor

## Built-in System

Mainboard Model	17MB400VS
Operating System	Android 9
CPU	Quad-Core ARM Cortex-A55
GPU	ARM Mali-G31 MP2
Storage	16 GB eMMC
Memory	2 GB DDR4
Wired	10/100/1000 Mbps Ethernet
WiFi	WiFi 5 (802.11 a/b/g/n/ac)
Additional Storage	Micro SD (up to 1TB)
HTML5 Browser	Vewd

## Rear I/Os

Video Input	4xHDMI2.0, 1xUSB-A 3.0, 1xUSB-A 2.0, 1xUSB-A 2.0 (Internal), 1x Micro USB
Video Output	1xHDMI2.0
Audio Output	Headphone, Optic SPDIF
External Control	RS232 (3.5mm jack green), Gigabit Ethernet (RJ45), Service (RJ12)
External Sensor	RJ12

## Mechanical

Product Dimensions (WxDxH)	963 x 63 x 555 mm
----------------------------	-------------------

Package Dimensions (WxDxH)	1050 x 178 x 718 mm
Product Weight	10.4 kg
Package Weight	13.5 kg
Vesa Mounting	200 (W) x 200 (H) mm M6
Bezel Width	B: 9 mm, T/L/R: 6 mm

## Environmental Conditions

Operating Temperature	0-40°C
Operating Humidity	10-90%

## Power

Power Supply	110 VAC - 240 VAC - 50/60 Hz
--------------	---------------------------------

## Power Consumption

Typical	127 W
Maximum	160 W
Deep Standby	≤0.5 W

## Features

Main Features	HTML5 CMS Launcher, Android CMS Launcher, Open Content Management Support, Scheduler, USB- Autoplay, Auto-Launch, HDMI-CEC, HDMI-Wakeup, Auto-switch on Failover, Panel Lock, OSD and UI Rotation, Video Rotation, NoSignalPowerOff, Pixel shift, Scheduler, Videowall support, Remote control via LAN, Real Time Clock, Crestron Connected, SNMP
Mechanical Features	Joystick, Rocker Switch, Detachable Power Cable, Detachable Logo, Internal USB Cover
Speaker	2x8 W

## Accessory

Standard	QSG, IB, Power cord, Remote control unit, RC battery, Mounting kit, IR extender cable
----------	--

## Certification

Safety	Yes
EMC	Yes
CE	Yes