

# Interactive Flat Panel IFD65TH752/3

# VESTEL



## Key Features



Crestron Connected certification complements VESTEL's presence with inside the corporate, retail, government, better training and hospitality markets, all of which use expert AV controls. As those sectors hold to evolve with growing necessities for simple-to-use merchandise, seamless integration, dependable answers and community connectivity.



Available in a variety of large screen sizes, the IFD range gives customers the options to choose exactly what they need for their room size.



Teachers, students or any user can share their screen efficiently and conveniently in the classroom or meeting room via EShare application. This application can connect any operating system and show up to 4 different screens at the same time.



Android gives teachers one touch access for lessons and collaboration tools including whiteboard, web browser, apps library, and native wireless screen sharing.



Automatic palm erasing function allows teachers and students to simplify the white board experience with smooth writing and erasing.

## Display

|                          |   |
|--------------------------|---|
| Screen Size              | 65"   |
| Panel Technology         | Direct-Type LED                                       |
| Backlight Type           | 350 cd/m²   |
| Native Resolution        | UHD: 3840 x 2160 - HDR10                              |
| Contrast Ratio (typical) | 1200:1  |
| Dynamic Contrast Ratio   | 35000:1   |
| Panel Life Time ( Min. ) | 30.000 hrs  |
| Life Time (typical)      | 8 ms  |
| Active Area (H x V)      | 1428 x 804 mm   |
| Pixel Pitch (H x V)      | 0.372 x 0.372 mm                                      |
| PPI (pixel per inch)     | 68  |
| Viewing Angle            | 178° Vert., 178° Hor.<br>(89U/89D/89L/89R) @<br>CR>10 |
| Color Value              | 1.07 B (10-bit)                                       |
| Screen Treatment         | 2H  |
| Haze Level               | 8%  |
| Refresh Rate             | 60 Hz   |
| Front Type               | Touch Bezel   |
| Orientation              | Horizontal  |
| Operation Hours          | 16/7 Panel  |
| Area of Usage            | Indoor  |

## Built-in System

|                 |         |
|-----------------|---------|
| Mainboard Model | MB135VS |
|-----------------|---------|

## Rear I/Os

|                  |   |
|------------------|---|
| RGB Input        | VGA(DE-15F)   |
| RGB Output       | N/A   |
| Video Input      | 3xHDMI2.0, 2xUSB2.0,<br>USB2.0(Internal), 1xMicroSD |
| Video Output     | HDMI2.0   |
| Audio Input      | Line In L/R   |
| Audio Output     | Headphone, Optic SPDIF                              |
| External Control | RS232(DE-9F),<br>2*Ethernet(RJ45),<br>Service(RJ12) |
| External Sensor  | RJ12  |

## Touch Interactivity

|                          |   |
|--------------------------|---|
| Type of Touch Technology | Infrared (IR) Tech. - 10<br>Points  |
| Sensitivity              | Any touch with finger, gloved<br>hand or pointer                          |
| Connectivity             | HID, TUIO, Flash  |
| Compatibility            | Windows®7,Windows®8,<br>Windows®10, Vista, XP,<br>Mac® OS, Linux, Android |
| Orientation              | Landscape support   |

|                        |                            |
|------------------------|----------------------------|
| Calibration            | No need                    |
| Accuracy               | 90% <                      |
| Reporting Rate         | up to 450 fps              |
| Glass Type             | Anti Glared (AG), Tempered |
| Frame Rate             | up to 450 fps              |
| Communication          | USB 2.0                    |
| Power Supply Mode      | USB                        |
| Supply Voltage         | DC 5V +/- 5%               |
| Average Current        | < 400 mA                   |
| Response Time          | < 10 ms                    |
| Touch Accuracy         | +/- 2 mm (over 90% area)   |
| Touch Durability       | Unlimited                  |
| HID Compatibility      | Yes USB                    |
| Object Sizes for Touch | 5 mm                       |

## Mechanical

|                            |                        |
|----------------------------|------------------------|
| Product Dimensions (WxDxH) | 1507 x 118 x 882 mm    |
| Package Dimensions (WxDxH) | 1756 x 265 x 1100 mm   |
| Product Weight             | 38.6 kg                |
| Package Weight             | 48 kg                  |
| Vesa Mounting              | 400 x 400 mm           |
| Bezel Width                | B:38  T:38   L/R:38 mm |

## Environmental Conditions

|                       |             |
|-----------------------|-------------|
| Operating Temperature | +40°C / 0°C |
| Operating Humidity    | 90%         |

## Power

|              |                   |
|--------------|-------------------|
| Power Supply | 110 VAC - 240 VAC |
|--------------|-------------------|

## Power Consumption

|              |        |
|--------------|--------|
| Typical      | 240 W  |
| Maximum      | 200 W  |
| Deep Standby | ≤ 0.5W |

## Features

|                     |   |
|---------------------|---|
| Main Features       | USB-Autoplay, Auto-switch<br>on Failover, Control Button<br>Lock, HDMI Wake-Up  |
| Mechanical Features | IR Touch, Joystick, IR<br>Extender Support, Rocker<br>Switch, Detachable power<br>cable, Carrying handles,<br>Detachable logo positioning,<br>Cable Holders |
| Optional Features   | OPS Compliance  |
| Speaker             | 2 x 8 W   |

## Accessory

|          |  |
|----------|--|
| Standard | QSG, Instruction Book,<br>Power Cord, Remote Control,<br>RC Battery, Mounting Kit,<br>Extension Brackets, IR<br>Extender Cable |
|----------|--|

## Certification

|                    |     |
|--------------------|-----|
| Safety             | YES |
| EMC                | YES |
| CE                 | YES |
| Reability Approval | YES |